

F135A.2.22

	15°			
MAX.	3075	2120	1600	
4650	4,45	6,25	8,25	

F135A.2.23

	15°						
MAX.	2900	1960	1440	1140	865	675	520
4450	4,50	6,35	8,30	10,35	12,55	14,75	16,95
•.23 L152							
					530	455	395
					13,00	14,75	16,55
•.23 L153							
					465	390	335
					13,10	14,80	16,65
•.23 L154							
					410	335	275
					13,20	14,90	16,70

F135A.2.24

	15°						
MAX.	2730	1800	1290	985	805	620	480
4200	4,60	6,45	8,40	10,45	12,55	14,75	16,95
•.24 L152							
					265	225	195
					15,15	16,85	18,65
•.24 L153							
					200	160	135
					15,20	16,95	18,75
•.24 L154							
					145	105	75
					15,30	17,00	18,85

F135A.2.25

	15°						
MAX.	2570	1655	1145	845	660	550	425
4000	4,65	6,50	8,45	10,50	12,65	14,75	16,95
•.25 L102							
					140	115	105
					17,55	19,35	21,15

F135A.2.26

	15°						
MAX.	2435	1530	1025	725	540	435	365
3800	4,75	6,60	8,55	10,60	12,70	14,85	16,95

C VERSION

F135AC.2.23

	15°						
MAX.	3575	2585	1810	1385	1045	810	640
5900	3,75	5,05	7,00	9,05	11,25	13,45	15,65

F135AC.2.24

	15°						
MAX.	3390	2425	1655	1230	980	760	595
5750	3,85	5,15	7,10	9,15	11,25	13,45	15,65
•.24 L152							
					405	345	305
					13,85	15,55	17,35
•.24 L153							
					345	285	240
					13,90	15,65	17,45
•.24 L154							
					290	230	185
					14,00	15,70	17,55

F135AC.2.25

	15°						
MAX.	3220	2270	1510	1090	840	690	540
5600	3,90	5,20	7,15	9,20	11,35	13,45	15,65

F135AC.2.26

	15°						
MAX.	3065	2135	1385	970	720	575	485
5450	4,00	5,30	7,25	9,30	11,40	13,55	15,65